



-- Concealed splice plates are provided with factory applied non-curing sealant strips.

-- Actual coping width (in to in) is actual wall width plus $\frac{5}{8}$ " (16 mm).

-- Unless otherwise noted, fabrication of miters and accessories are furnished standard utilizing a non-penetrating quicklock joint, then factory sealed watertight.

-- Wood nailer required for FM approval or ANSI/SPRI ES-1 rating.

-- Welded Miters and Accessories

Check one ☐ Required (surcharge) ☐ Not applicable

MATERIAL:

___ 24 Ga. (0.65 mm) Galv.

___ 22 Ga. (0.85 mm) Galv. Color: _____

___ .050" (1.27 mm) Alum.

___ .063" (1.60 mm) Alum. Finish: _____

___ OTHER _____

Fabrication will proceed only after receipt of signed print approval.

Print Approval:

Architect and/or contractor shall verify all dimensions, sizes and quantities. All products to be installed in strict accordance with Petersen Aluminum's printed instructions.

Approved by: _____

Date: _____

QUANTITIES:

_____ Lineal Feet (12'-0" (3.65 m) Lengths)

_____ Outside Miters @ (_____)°

_____ Inside Miters @ (_____)°

_____ Right End Caps

_____ Left End Caps

PROJECT:

ARCHITECT:

ROOFING CONTRACTOR:

REPRESENTATIVE/DISTRIBUTOR: